











<i>Standard</i>	Capacity	Internal dimensions		Door opening		Max. payload Tara weight	Max. EUR pallets
20' Dry Cargo (DC) 	33 cbm	Lenght	5.898 mm	Width	2.340 mm	28.160 kgs 2.230 kgs	11
		Height	2.393 mm	Height	2.280 mm		
40' Dry Cargo (DC) 	67 cbm	Lenght	12.035 mm	Width	2.340 mm	26.760 kgs 3.700 kgs	25
		Height	2.393 mm	Height	2.280 mm		
40' High Cube Dry Cargo (HC DC) 	76 cbm	Lenght	12.035 mm	Width	2.340 mm	26.750 kgs 3.800 kgs	25
		Height	2.695 mm	Height	2.577 mm		
45' High Cube Dry Cargo (HC DC) 	85 cbm	Lenght	13,556 mm	Width	2,340 mm	28.280 kgs 4.800 kgs	27
		Height	2,695 mm	Height	2,577 mm		

<i>Reefer</i>	Capacity	Internal dimensions		Door opening		Max. payload Tara weight	Max. EUR pallets
20' Reefer (RF) 	28 cbm	Lenght	5.451 mm	Width	2.286 mm	27.490 kgs 2.990 kgs	10
		Height to load line	2.157 mm	Height	2.238 mm		
40' High Cube Reefer (HC RF) 	67 cbm	Lenght	11,577 mm	Width	2,286 mm	28,350 kgs 4.150 kgs	23
		Height to load line	2,378 mm	Height	2,535 mm		

<i>Open Top</i>	Capacity	Internal dimensions		Top opening		Max. payload Tara weight
20' Open Top (OT) 	32 cbm	Lenght	5.919 mm	Lenght	5.425 mm	28.230 kgs 2.177 kgs
		Width	2.340 mm	Width	2.223 mm	
		Height	2.286 mm			
40' Open Top (OT) 	64 cbm	Lenght	12.029 mm	Lenght	11.909 mm	26.580 kgs 3.800 kgs
		Width	2.340 mm	Width	2.223 mm	
		Height	2.286 mm			

<i>Flat Rack</i>	Max. height of cargo	Floor dimensions		Dimensions between stanchions		Max. payload Tara weight
20' Flat Rack (FR) 	2.245 mm	Lenght	5.966 mm	Lenght	5.702 mm	27.150 kgs 2.850kgs
		Width	2.365 mm	Width	2.200 mm	
		Height of floor	0.370 mm			
40' Flat Rack (FR) 	2.275 mm	Lenght	12.060 mm	Lenght	11.660 mm	39.300 kgs 5.700 kgs
		Width	2.365 mm	Width	2.200 mm	
		Height of floor	0.648 mm			